

PLANT DATA SHEET

For any enquires please contact office@civilsydney.com.au

23 Channel Road Mayfield West NSW 2304 Ph. (02) 4058 1800 www.civilsydney.com.au

ABN 15 068 316 432

Make: Year:	Junttan 1986	Model: Plant ID:	PM20 PN010
Plant Description:		Capabilities:	
The Junttan PM20 is a hydraulic piling rig for driving steel, concrete & timber piles. The rig can self-pitch piles up to 15m long without the need for predrilling. It boasts increased manoeuvrability comparative to our larger PM20LC due to its smaller stature and weight, making it superior on difficult to navigate sites. The PM20 houses a 5T ram weight that can be deployed at a height of 1m.		DrivSte	-cast Concrete ven Timber el Casing el Piles







PLANT DATA SHEET

For any enquires please contact office@civilsydney.com.au

23 Channel Road Mayfield West NSW 2304 Ph. (02) 4058 1800 www.civilsydney.com.au

ABN 15 068 316 432

Operational	52,000kg	1 81 2	
Weight:	_		
Traveling Length:	17,400mm	00 4 0	
(Transport)		4 10	
Working Length:	11,400mm	1 1 0	
(Centre of Pile to rear of counterweight)		1 113	
Traveling Width:	3,100mm	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
(Transport)			
Working Width:	4,200mm		
(Tracks Extended) Traveling Height:	3,750mm	126000	
(Transport)	3,73011111		
Working Height:	22,000mm		
(With & without leader	,		
extension) Aux Winch	5,000kg		
7 10111 7 1111011	(With Load cell)		
Capacity:			
Hydraulic Hammer			
Model:	HHK 5A	4	
Max Stroke:	1,000mm	3920	
Blow Rate:	40 - 100		
(Per minute)	5 000kg	(a) 100.1.14200 ala 14200.1.3100 al	
Ram Weight:	5,000kg	11	
Total mainlet	0.70016	₹ ₩	
Total weight:	8,700Kg	S TH	
Additional Features:			
Annual 'Pile Safe' & NDT		¥ 800	
ROPS & FOPS		(3100	
360deg Cameras		-4100)	
Service history and plant RA		22370	
Enviro PANOLIN Hydraulic oil			
E- Stops & Load Cells			
Access Handrails and platforms			
Aux Line Restraint Device OEM			